



VID29-04/07 Precaution of Pointer Assembly 指針裝配要點

Description 描述	Diagram 圖解	Specification 標準		Possible problems when over limit 超标后可能引起的问题	Remarks 备注
		Limit 極限	Unit 單位		
Maximum Push On Force 最大壓力		180 max.	N	Wire damaged/ Wire broken/ Gear damage/ Abnormal Noise/ Gear & shaft mounting is damaged 断线\线伤\齿伤\杂音\齿轮与指针轴埋注受伤	Proper fixing motor on PCB. Proper supporting during assembly. 电机需正确装上PCB；
Minimum Assembly Support 最小裝配支持		Dia.25 min.	mm	Wire damaged/ Wire broken/ Gear damage/ Abnormal Noise/ Gear & shaft mounting is damaged 断线\线伤\齿伤\杂音\齿轮与指针轴埋注受伤	Concrete base support should be located within +/- 1.0mm concentricity to the motor
Maximum Pull Out Force 最大撥出力		90 max.	N	Wire damaged/ Wire broken/ Gear damage/ Abnormal Noise/ Gear & shaft overmoulding damage/ Low pull out force 断线\线伤\齿伤\杂音\ 齿轮与指针轴埋注受伤\低拔出力	Repetitive push & pull force should also be avoided. This could weaken overmoulding force between gear and shaft, then it induce low pull out force.
Maximum Perpendicular Force 最大橫向力		13 max.	N	Output shaft bend/ Non-concentric rotation of output shaft 轴弯\转动晃动	Excess perpendicular force should be avoided to bend the shaft. 需避免过大橫向力，防止轴弯。
Maximum Force Inclination 最大力傾斜度		4.1max.	degree	Output shaft bend/ Non-concentric rotation of output shaft 轴弯\转动晃动	Excess inclination of applied force should be avoided to bend the shaft. 施加外力時,需避免外力过大傾斜，防止轴弯。
Maximum Straightness Deviation of Pointer Assembly 最大指針裝配垂直度偏差		0.10 max.	mm	Output shaft bend/ Non-concentric rotation of output shaft. 轴弯\转动晃动	Pointer straightness should be maintained within 0.1mm during assembly. Excess inclination could induce excess perpendicular force and bend the shaft. 當裝配時
Maximum Assembly Speed 最高裝配速度		3 max.	mm/sec	Gear damage/ Gear & shaft mounting is damaged 齿伤\齿轮与指针轴埋注受伤	Excess assembly speed could induce excess force on gears. 裝配速度太快會令齿轮受力过大。
Maximum External Torque 最大外加扭力		40 max.	mNm	Gear damage/ Gear & shaft overmoulding damage / Low pull out force / Stopper damage (360 Degree Rotate) 齿伤\齿轮与指针轴埋注受伤\低拔出力\限位受伤	Excess external torque applied on shaft would weaken overmoulding force between gear and shaft. It induce low pull out force. 过量外加扭力，齿轮和轴的埋注会弄伤。 Repetitive external torq
Maximum Imposed Acceleration 最高外加加速度		1000 max.	rad/s ²	Gear damage 齿伤	Excessive imposed acceleration would induce excessive force on gears, it must be avoided. 过高外加加速度,能引起齿轮上產生过大應力，必須避免。